

SAFETY DATA SHEET

According to OSHA Hazcom Standard 29 CFR 1910.1200

XTeer TOP C5 0W-20 (ENG)

Date of issue: 2023-01-30 Revision date: Not applicable Version: 2.0

1. IDENTIFICATION

A. Product name

- XTeer TOP C5 0W-20 (ENG)

B. Recommended use and restriction on use

- General use : Automotive Engine oil

- Restriction on use : Do not use for purposes other than recommended.

C. Manufacturer / Supplier / Distributor information

o Manufacturer information

- Company name : HD HYUNDAI OILBANK

- Address : 17-10, Mabuk-ro 240beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea

- Emergency telephone number : 02-500-4500

o Supplier/Distributer information

- Company name : HD HYUNDAI OILBANK

- Address : 17-10, Mabuk-ro 240beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea

- Emergency telephone : 02-500-4500

number : 02-500-4500

2. HAZARD IDENTIFICATION

A. GHS Classification

- Not applicable

B. GHS label elements

o Hazard symbols

Not applicable

o Signal words

- Not applicable

o Hazard statements

- Not applicable

$\circ \ Precautionary \ statements \\$

1) Prevention

- Not applicable

2) Response

- Not applicable

3) Storage

- Not applicable

4) Disposal

- Not applicable

C. Other hazards which do not result in classification

- Not available

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | Trade names and Synonyms | CAS No. | Content(%) |
|---------------------------------------|--------------------------|------------|------------|
| Distillates (petroleum), hydrotreated | Emulsifiable oil | 64742.54.7 | 50 67 |
| heavy paraffinic | | 64742-54-7 | 58 ~ 67 |

| 1-Decene, homopolymer, hydrogenated | Hydrogenated decene homopolymer | 68037-01-4 | 17 ~ 28 |
|---|---|------------|---------|
| Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based | Not available | 72623-87-1 | 7 ~ 15 |
| Distillates (petroleum), solvent- dewaxed heavy paraffinic | Heavy paraffinic base lube stock; Mineral oil, petroleum distillates, solvent dewaxed heavy paraffinic (severe solvent-refining and/or hydrotreatment); Solvent dewaxed heavy paraffinic distillate; Adriatic spindle oil | 64742-65-0 | 1 ~ 5 |
| 4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt | zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) | 2215-35-2 | ~ 1 |
| Phosphorodithioic acid mixed O,O- bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts | Phosphorodithioic acid, O,O-bis(1,3-dimethylbutyl and isopropyl)esters, zinc salts | 84605-29-8 | ~ 1 |
| Distillates (petroleum), solvent- dewaxed light paraffinic | Solventdewaxed light paraffinic distillate (petroleum) | 64742-56-9 | ~ 1 |

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.

C. Inhalation contact

- Take specific treatment if needed.
- When exposed to large amounts of steam and mist, move to fresh air.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media

- Avoid use of water jet for extinguishing
- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Avoid inhalation of materials or combustion by-products.
- Cool containers with water until well after fire is out.
- Do not approach the tank surrounded by fire until it is extinguished.
- In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn.
- Keep unauthorized personnel out.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Do not touch spilled material. Stop leak if you can do it without risk.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Move container to safe area from the leak area.

- Must work against the wind, let the upwind people to evacuate.
- Remove all sources of ignition.

B. Environmental precautions

- If large amounts have been spilled, inform the relevant authorities.
- Prevent runoff and contact with waterways, drains or sewers.

C. Methods and materials for containment and cleaning up

- Appropriate container for disposal of spilled material collected.
- Dike for later disposal.
- Disposal of waste shall be in compliance with the Wastes Control Act
- Large spill: Stay upwind and keep out of low areas. Dike for later disposal.
- Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Avoid contact with incompatible materials.
- Avoid direct physical contact.
- Comply with all applicable laws and regulations for handling
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.

B. Conditions for safe storage, including any incompatibilities

- Avoid direct sunlight.
- Check regularly for leaks.
- Do not apply any physical shock to container.
- Do not apply direct heat.
- Do not use damaged containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

o ACGIH TLV

- [Distillates (petroleum), hydrotreated heavy paraffinic]: TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic]: TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-dewaxed light paraffinic]: TWA 5 mg/m3, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)

o OSHA PEL

- Not applicable

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

$\circ \ Respiratory \ protection$

- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Consider warning properties before use.
- For Unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Respiratory protection is ranked in order from minimum to maximum.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

o Eye protection

- Provide an emergency eye wash station and quick drench shower in the immediate work area.

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.

o Hand protection

- Wear appropriate chemical resistant glove.

o Skin protection

- Wear appropriate chemical resistant protective clothing.

$\circ \ Others$

- Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

| A. Appearance | |
|---|-------------------|
| - Appearance | Liquid |
| - Color | Amber |
| B. Odor | mild |
| C. Odor threshold | No data available |
| D. pH | No data available |
| E. Melting point/Freezing point | No data available |
| F. Initial Boiling Point/Boiling Ranges | Not available |
| G. Flash point | > 220°C |
| H. Evaporation rate | No data available |
| I. Flammability(solid, gas) | No data available |
| J. Upper/Lower Flammability or explosive limits | No data available |
| K. Vapour pressure | No data available |
| L. Solubility | No data available |
| M. Vapour density | No data available |
| N. Specific gravity(Relative density) | 0.848 |
| O. Partition coefficient of n-octanol/water | No data available |
| P. Autoignition temperature | No data available |
| Q. Decomposition temperature | No data available |
| R. Viscosity | 8.2 cSt at 100°C |
| S. Molecular weight | No data available |

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with incompatible materials and condition.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- $\circ \ Respiratory \ tracts$
 - Not available
- $\circ \ Oral$
 - Not available
- $\circ \; Eye {\cdot} Skin$
 - Not available

B. Delayed and immediate effects and also chronic effects from short and long term exposure

o Acute toxicity

* Oral

- Product (ATEmix): >5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic]: LD50 > 5000 mg/kg Rat (ECHA)
- [1-Decene, homopolymer, hydrogenated]: LD50 > 5000 mg/kg Rat (OECD TG 401, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based]: LD50 >5000 mg/kg Rat (Read-across Cas No. 64742-56-9) (OECD TG 401, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LD50 > 5000 mg/kg Rat (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: LD50 5000 mg/kg Rat, (LD50 2000 ~ 5000 mg/kg Rat (male/female, GLP)(ECHA))
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts]: Rat(F) LD50=3.1g/kg(3100mg/kg)(OECD Guideline 401)(ECHA).Rat LD50=2000~4000mg/kg)(IUCLID).Rat LD50=3.2gm/kg(RTECS)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LD50 > 5000 mg/kg Rat (ECHA)

* Dermal

- Product (ATEmix): 2000mg/kg < ATEmix <= 5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic]: LD50 >5000 mg/kg Rabbit (ECHA)
- [1-Decene, homopolymer, hydrogenated]: LD50 > 2000 mg/kg Rat (OECD TG 402, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based]: LD50 > 5000 mg/kg Rabbit (Read-across Cas No. 64742-56-9) (OECD TG 402, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LD50 > 2000 mg/kg Rabbit (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: LD50 >3160 mg/kg Rabbit(ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts] : rat(F/M) LD50>2002mg/kg bw. no death(OECD Guideline 402, GLP)(ECHA), Rabbit LD50>3200mg/kg bw(ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic]: LD50 > 2000 mg/kg Rabbit (OECD Guideline 402 (Acute Dermal Toxicity),GLP) (EHCA)

* Inhalation

- Product (ATEmix): 20.0mg/L < ATEmix <= 50.0mg/L, Vapour, 4hr
- [Distillates (petroleum), nydrotreated neavy paratimic]: Aerosol LC3U > 5.55 mg/L 4 nr, Kat, Kead-across: CAS No. 04/41-88-4 (ECHA)
- [1-Decene, homopolymer, hydrogenated]: Aerosol LC50 < 4.8 mg/L 4 hr Rat Not classified (OECD TG 403, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : Aerosol LC50 > 5.53 mg/ ℓ 4hr No death Not classified (Readacross Cas No. 64741-88-4) (OECD TG 403, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Mist LC50 2.18 mg/ ℓ 4 hr Rat (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt] : dust LC50 >0.5 mg/ ℓ 4 hr Rat (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts] : Rat(F/M) 4h LC50 > 2.3 mg/L air. no death(OECD Guideline 403)(ECHA)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : Aerosol LC50 2.18 mg/ ℓ 4 hr Rat (OECD TG 403, GLP) (ECHA)

O Skin corrosion/irritation

- Not available
- o Serious eye damage/irritation
 - Not available

o Respiratory sensitization

- Not available

o Skin sensitization

- Not available
- o Carcinogenicity
 - * IARC
 - Not available
 - * OSHA
 - Not available
 - * ACGIH
 - Not available
 - * NTP
 - Not available

* EU CLP

- [Distillates (petroleum), hydrotreated heavy paraffinic]: Carc. 1B (Note L)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : Carc. 1B (Note L)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Carc. 1B (Note L)

- [Distillates (petroleum), solvent-dewaxed light paraffinic]: Carc. 1B (Note L)
- Not available

o Germ cell mutagenicity

- Not available
- o Reproductive toxicity
 - Not available
- o STOT-single exposure
 - Not available
- o STOT-repeated exposure
 - Not available
- o Aspiration hazard
 - Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

o Fish

- [Distillates (petroleum), hydrotreated heavy paraffinic]: LL50 > 100 mg/L, 96hr, Pimephales promelas (ECHA)
- [1-Decene, homopolymer, hydrogenated]: LL50 > 1000 mg/L 96 hr Oncorhynchus mykiss (OECD TG 203, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : $LL50 > 100 \text{ mg}/\ell 96 \text{ hr Pimephales promelas (OECD TG 203, GLP) (ECHA)}$
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic]: LC50 5000 mg/ ℓ 96 hr Oncorhynchus mykiss (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt] : LC50 25 mg/ℓ 96 hr Pimephales promelas (IUCLID), LC50 46 mg/ℓ 96 hr (Cyprinodon variegatus, OECD Guideline 203, GLP, read-across: 68457-79-4) (ECHA))
- $\ [Phosphorodithioic\ acid\ mixed\ O,O-bis(1,3-dimethylbutyl\ and\ iso-Pr)\ esters\ zinc\ salts]:\ Cyprinodon\ variegatus\ 96hr\ LC50=46\ mg/L\ (OECD\ Guideline\ 203,\ GLP)(read-across;\ 68457-79-4)(ECHA),\ Pimephales\ promelas\ 96hr\ LC50=10\sim100mg/L\ (OECD\ Guideline\ 203,\ GLP)(IUCLID)$
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : LC50 5000 mg/ℓ 96 hr Oncorhynchus mykiss (IUCLID)

Crustaceans

- [Distillates (petroleum), hydrotreated heavy paraffinic] : EL50 > 10000 mg/L, 48hr, Daphnia magna (ECHA)
- [1-Decene, homopolymer, hydrogenated]: EL50 > 1000 mg/L 48 hr Daphnia magna (OECD TG 202, GLP), NOELR 125 mg/L WAF 21 d Daphnia magna (OECD TG 211, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based]: ELSO > 10000 mg/t 48 hr Daphnia magna (OECD 1G 202) (FCHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : EC50 1000 mg/ℓ 48 hr Daphnia magna (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: EC50 6 mg/ ℓ 48 hr Daphnia magna (IUCLID) EL50 23mg/L, 48hr, OECD Guideline 202, GLP, read-across: 84605-29-8, ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts] : Daphnia magna 48hr LC50= $0.1\sim1mg/L$ (OECD Guideline 202, GLP)(IUCLID)
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : EC50 1000 mg/ ℓ 48 hr Daphnia magna (IUCLID)

o Algae

- [Distillates (petroleum), hydrotreated heavy paraffinic]: EC25 1152.9 mg/L, 96hr, Pseudokirchneriella subcapitata, NOEL >= 100 mg/L, 72hr (ECHA)
- [1-Decene, homopolymer, hydrogenated]: EL50 > 1000 mg/L 96 hr, NOELR 1000 mg/L 96 hr Raphidocelis subcapitata (OECD TG 201, GLP) (ECHA)
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based] : NOEL $\geq 100 > 100 \text{ mg}/\ell$ 72 hr Raphidocelis subcapitata (OECD TG 201) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : EC50 1000 mg/l 96 hr Scenedesmus subspicatus (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: EC50 5 mg/ ℓ 72 hr Selenastrum capricornutum(OECD Guideline 201, GLP, read-across:84605-29-8) (IUCLID), ErC50 24 mg/ ℓ 72 hr Scenedesmus subspicatus (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts] : (조류(Scenedesmus subspicatus) : EL50(72h)=21 mg/L, (OECD Guideline 201, GLP), 지수식)|※출처 : ECHA

B. Persistence and degradability

o Persistence

- [Distillates (petroleum), hydrotreated heavy paraffinic]: log Pow = 1.99 ~ 18.02 (20 °C) (ECHA)
- [1-Decene, homopolymer, hydrogenated]: log Pow > 6.5 (OECD TG 117, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : log Kow $3.9 \sim 6$ (Estimate) (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: log Kow 2.21 (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts] : $\log kow = 0.56(22 \, ^{\circ}C, \, pH \, 5)(OECD \, Guideline \, 107, \, GLP)(ECHA)$
- [Distillates (petroleum), solvent-dewaxed light paraffinic] : log Kow 3.9 \sim 6 (Estimate)

o Degradability

- [Distillates (petroleum), solvent-dewaxed light paraffinic] : (non-degradable, BIOWIN 1,2,5,6,7) (Estimate)

C. Bioaccumulative potential

o Bioaccumulative potential

- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: BCF 27600 (Estimate)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts]: BCF < 2000 (L/kg)
- [Distillates (petroleum), solvent-dewaxed light paraffinic]: BCF 5151 (L/kg wet-wt) (Estimate)

o Biodegradation

- [1-Decene, homopolymer, hydrogenated]: 7 % 28 d, Not readily biodegradable (OECD TG 301 B, GLP) (ECHA)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: 1.5 %, 28 day (Non-degradable, OECD TG 301B, GLP, read-across: 84605-29-8) (ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts]: 1.5%, 28 days (OECD Guideline 301 B, GLP)(ECHA)

D. Mobility in soil

- Not available

E. Other adverse effects

- [Distillates (petroleum), solvent-dewaxed heavy paraffinic]: fish: NOEC(Fathead Minnow) >5000 mg/L/7days (IUCLID)
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt]: crustaceans-Daphnia magna: NOEC-21d = 0.4 mg/L, OECD Guideline 211, GLP, Analogous substance:89605-29-8(ECHA)
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts]: Daphnia 21 d NOEC=46 mg/L (OECD Guideline 202 GLP)(ECHA)

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- It shall be treated by incineration
- Oil water separation technology shall be applied as pre-waste treatment if it is applicable
- Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them

B. Special precautions for disposal

- Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG CODE/IATA DGR)

- Not applicable

B. Proper shipping name

- Not applicable

C. Hazard Class

- Not applicable

D. IMDG CODE/IATA DGR Packing group

- Not applicable

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Air transport(IATA): Not subject to IATA regulations.
- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : Not available
- EmS SPILLAGE SCHEDULE: Not available

15. REGULATORY INFORMATION

A. National and/or international regulatory information

o POPs Management Law

- [Distillates (petroleum), hydrotreated heavy paraffinic]: Not applicable
- [1-Decene, homopolymer, hydrogenated]: Not applicable
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based]: Not applicable
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Not applicable
- [4-Methyl-2-pentanol hydrogen phosphorodithioate zinc salt] : Not applicable
- [Phosphorodithioic acid mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters zinc salts]: Not applicable
- [Distillates (petroleum), solvent-dewaxed light paraffinic]: Not applicable

o Information of EU Classification

* Classification

- [Distillates (petroleum), hydrotreated heavy paraffinic]: H350
- [Lubricating oils (petroleum), (C=20-50) hydrotreated neutral oil-based]: H350
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic]: H350
- [Distillates (petroleum), solvent-dewaxed light paraffinic]: H350

o U.S. Federal regulations

* OSHA PROCESS SAFETY (29CFR1910.119)

- Not applicable
- * CERCLA Section 103 (40CFR302.4)
 - Not applicable
- * EPCRA Section 302 (40CFR355.30)
 - Not applicable
- * EPCRA Section 304 (40CFR355.40)
 - Not applicable
- * EPCRA Section 313 (40CFR372.65)
 - Not applicable

$\circ \ \textbf{Rotterdam Convention listed ingredients}$

- Not applicable
- o Stockholm Convention listed ingredients
 - Not applicable
- o Montreal Protocol listed ingredients
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2023-01-30

C. Revision number and Last date revised

- Not applicable

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).